



In accordance with the European Standard EN 16630. Structure composed by structural posts sized 200x120mm, made of 3mm S235J-grade steel. Anchoring posts sized 300x300mm, made of 10mm S235J-grade steel, with pilot holes for anchoring to the ground or to anchors. Casings and surface details made of laser-cut, 3–10mm S235J-grade steel. Flywheel casing boxed in 14mm plain green HDPE, with UV-proof pigmentation and rounded edges. Flywheel casing sealed with a 1mm plate of SAE 304 stainless steel. Ball spline assembly for disc rotation, with steel bearings sized 48mm, in watertight casings. Handles made of black polyethylene, sized 25mm x 15mm. Assembly system with 8.8 galvanized steel bolts and self-locking nuts. Nut caps made of engineering plastic as required by law. Finishing of fitness equipment: sandblasting, protective primer, bed-dip coating in grey and black RILSAN. Finishing of structural posts: sandblasting, cold galvanizing, RAL 9005 powder coating.



cm 863x590x1750h
INGOMBRO MAX



< 1m
ALTEZZA CADUTA



1
NUMERO UTILIZZATORI



1 h
TEMPO DI ASSEMBLAGGIO



cm 370x360
SPAZIO MINIMO



m² 0,00
AREA IMPATTO

Planimetria / Planimetry

