



Certified by the German TÜV – SÜD Product Service Institute according to the European Standard in force EN 1176. Structure made of painted electro galvanized steel, baked finishing at 180°C. Components: Rocking beam in painted electro-galvanized steel section Ø 60 mm equipped with tubular handles section Ø 30 mm. Coloured polyethylene seats (PEHD) 15 mm thick, pantographed without sharp edges. The oscillation mechanism is through a fulcrum on teflon bearing and consists of a hot-dip galvanised central steel frame, section Ø 60 mm, baked finishing at 180°C. The damping device is made of fabric-reinforced rubber. Assembly system with 8.8 galvanized steel bolts and self- locking nuts. Coloured nylon cap nuts as required by law. Brackets for ground anchoring system.

<p>cm 256x40x68h <b>INGOMBRO MAX</b></p>	<p>cm 68 <b>ALTEZZA CADUTA</b></p>	<p>2-8 years <b>ETÀ D'USO</b></p>
<p>1 h <b>TEMPO DI ASSEMBLAGGIO</b></p>	<p>2 <b>NUMERO UTILIZZATORI</b></p>	<p>cm 450x250 <b>SPAZIO MINIMO</b></p>
<p>m<sup>2</sup> 12 <b>AREA IMPATTO</b></p>		

Planimetria / Planimetry

