





In accordance with the European Standard EN 16630. **LAT MACHINE:** Structure composed by structural posts sized 200x120mm, made of 3mm S235Jgrade steel; Anchoring posts sized 300x300mm, made of 10mm S235Jgrade steel, with pilot holes for anchoring to the ground or to anchors; Casings and surface details made of laser-cut, 3–10mm S235J-grade steel; Seating made of 19mm two-colour HDPE, with UV-proof pigmentation, rounded edges, and non-slip textured surface; Handles sized 40mm, made of 2mm S235J-grade steel; Frame made of 3mm S235J-grade steel tubing sized 50x30mm.; Steel bearings sized 37mm, in watertight casings; Vibration damper and limit stop sized 50mm and made of rubber, with M10 threaded stud. **PECTORAL MACHINE:** Structure composed by structural posts sized 200x120mm, made of 3mm S235Jgrade steel; Anchoring posts sized 300x300mm, made of 10mm S235Jgrade steel, with pilot holes for anchoring to the ground or to anchors; Casings and surface details made of laser-cut, 3–10mm S235J-grade steel; Seating made of 19mm two-colour HDPE, with UV-proof pigmentation, rounded edges, and non-slip textured surface; Handles sized 40mm, made of 2mm S235J-grade steel; Frame made of 3mm S235J-grade steel tubing sized 50x30mm.; Steel bearings sized 37mm, in watertight casings; Vibration damper and limit stop sized 50mm and made of rubber, with M10 threaded stud. Assembly system with 8.8 galvanized steel bolts and self- locking nuts. Nut caps made of engineering plastic as required by law. Finishing of fitness equipment: sandblasting, protective primer, bed-dip coating in grey and black RILSAN. Finishing of structural posts: sandblasting, cold galvanizing, RAL 9005 powder coating.

 cm 2040x660x1950  
**INGOMBRO MAX**

 < 1m  
**ALTEZZA CADUTA**

 1 h  
**TEMPO DI ASSEMBLAGGIO**

 2  
**NUMERO UTILIZZATORI**

 cm 510x370  
**SPAZIO MINIMO**

 m<sup>2</sup> 0,00  
**AREA IMPATTO**

Planimetria / Planimetry

